



THE CHOICE OF EXPERTS

752-C HEAVY DUTY OFFSET HARROW WITH 10.5" SPACING

TECHINCAL DATA	
Main frame:	4" x 6" (102 x 152 mm) High resistance Rectangular Hollow Section (RHS)
Disc gang frame:	4" x 10" (102 x 254 mm) High resistance Rectangular Hollow Section (RHS)
Hitch bar:	Self-aligned, with centered grading crank and adjustments quadrant
Depth control wheels:	Four-wheel drive, 7.5" (19cm) x 16" (40cm) with 6 lug nuts. (from 40 to 24 discs)
Gang axle bolts:	C-1060 - 1 1/2" (38 mm) Steel bar
Spools:	Grey iron.
Mod. 752-C High impact nodular steel bearings	Oil-bath conical ball bearings. For radial and axial loads with a 15,803 lb (7183 kg) load capacity
SAE 15B37H boron alloy steel discs	Notched front gang and flat rear gang (all flat optional). 1/4" x 26" (66 cm x 6mm) plain center, 1/4" x 28"(71 cm x 6 mm) and 5/16 x 30" (76 cm x 8 mm) .
Disc scrapers:	Heavy weight and adjustable.
Lifting system:	Hydraulic control.
Gangs adjustable angle:	From 26° to 46°.
Transportation clearance:	9.0" (230 mm) It varies according to disc type.
Disc gang lateral adjustment:	Rear gang.

*Small Frame from 12 to 18 discs *Medium Frame from 20 to 40 discs *Large Frame from 42 to 48 discs

Working width (mm)	No. of discs	Discs diameter (in)(mm)	Power (Hp)	Distance between discs (in) (mm)	Axle measurements (in) (mm)	No. of bearings or ball bearings	Weight in kg Ø26-Ø28-Ø30
1592	12	Ø 26" x 1/4" (Regular) 660 mm x 6mm Ø 28" x 1/4" (Opt.) 710 mm x 6 mm Ø 30" x 5/16" (Opt.) 760 mm x 8 mm	75	10 1/2" 266 mm	1 1/2" 38 mm Square	4	1347-1380-1497
1866	14		85			4	1507-1546-1682
2130	16		100			6	1667-1711-1867
2362	18		100			6	1753-1803-1978
2710	20		120			8	1819-1875-2069
2857	22		120			8	1889-1950-2164
3140	24		130			8	2130-2194-2486
3350	26		130			8	2307-2377-2693
3640	28		140			10	2485-2560-2901
3851	30		140			10	2555-2639-2930
4170	32		160			12	2661-2749-3139
4345	34		160			12	2731-2826-3156
4590	36		180			12	2796-2895-3334
4840	38		180			12	2866-2972-3341
5250	40		200			12	2966-3080-3542
5336	42		200			12	3342-3459-3867
5585	44		240			14	3412-3535-3961
5837	46		260			14	3482-3610-4057
6089	48	280	14	3708-3842-4308			

NOTE: Specifications may vary without previous notice
 Pictures may include optional equipment and accessories and may not include all the regular equipment.

(*) Depending on soil type and conditions.

ABASTECEDORA DE MAQUINARIA Y SERVICIO, S.A. DE C.V.

EXCLUSIVE EXPORT MANAGER
 DISTRIBUTION:
 WALPECO, 1100 SOUTH 56TH AVE.,
 HOLLYWOOD, FLORIDA 33023 USA
 PH: 954-983-4511
 EMAIL:WALPECO@WALPECO.COM

FACTORY & MAIN OFFICE
 FCO. VILLA NO. 708 COL. GREMIAL
 AGUASCALIENTES, AGS. ZIP CODE. 20030
 MEXICO



**752-C HEAVY DUTY OFFSET HARROW
WITH 10.5" SPACING**

THE CHOICE OF EXPERTS



**Nodular steel
Oil-bath bearing**

