

Over 100 Years  
of Sugar Cane  
Innovation



# HODGE

## Offset Disc Harrow Heavy Duty



### Heavy Duty Offset Disc Harrow Specifications:

- Available in 24, 28, 32, 36, 40 & 44 Disc Models - Most Common Harrow for Cane Farming
- Cut Widths: 24disc-2.9m, 28disc-3.4m, 32disc-3.9m, 36disc-4.4m, 40disc-4.9m, 44disc-5.4m
- 28" x 6mm Discs Spaced 10" Apart & Steel Spacers (not cast)
- Main Frame 150x150mm Heavy Box with Adjustable Front Drawbar & Rear Drawbar
- Parallel Lift Spring Mechanism to Level Machine in Travel or Working Positions
- 40mm Square 1045 Grade Axles with Double UNF Nuts Each End.
- 9, 13 or 17 Greaseable Japanese NTN Flangette Bearings (Option of Extra Bearings)
- Fill-in Disc, Bolt On Bearing Dropper & Disc Scrapers
- 11.5/80-15.3 16 ply Wheels with Hydraulic Ram for Lift. Dual Wheels on 36 - 44disc models
- Bolt-Up Gang Angle On 200x100mm Heavy Box Gang Beams.
- Optional Hydraulic Gang Angle Change System with Phasing Rams & Roller Cage
- Suit Tractors from 130-220hp.

**HODGE INDUSTRIES** Phone: (+61) 7 4955-0500

Email: [sales@hodge.com.au](mailto:sales@hodge.com.au) Website: [www.hodge.com.au](http://www.hodge.com.au)

Address: 20 Spiller Avenue, (PO Box 99), Mackay, Qld, Australia, 4740

312000 OFFSET HEAVY DUTY