

Over 100 Years  
of Sugar Cane  
Innovation



# HODGE

## Offset Disc Harrow Standard Duty



### Standard Duty Offset Disc Harrow Specifications:

- Available in 20, 24, 28 & 32 Disc Models
- Cut Widths: 20disc - 2.13m, 24disc - 2.57m, 28disc - 3m, 32disc - 3.46m
- 26" x 6mm Discs Spaced 9" Apart & Steel Spacers (not cast)
- Main Frame 125x125mm Heavy Box with Adjustable Front Drawbar & Rear Drawbar
- Parallel Lift Spring Mechanism to Level Machine in Travel or Working Positions
- 40mm Square 1045 Grade Axles with Double UNF Nuts Each End.
- 9 Greaseable Japanese NTN Flangette Bearings (Option of Extra Bearings)
- Fill-in Disc, Bolt On Bearing Dropper & Disc Scrapers
- 245/75R16LT Wheels with Hydraulic Ram for Lift.
- Bolt-Up Gang Angle On 125x75mm Box Gang Beams
- Optional Hydraulic Gang Angle Change System with Phasing Rams & Roller Cage
- Suit Tractors from 90-140hp.

**HODGE INDUSTRIES** Phone: (+61) 7 4955-0500

Email: [sales@hodge.com.au](mailto:sales@hodge.com.au) Website: [www.hodge.com.au](http://www.hodge.com.au)

Address: 20 Spiller Avenue, (PO Box 99), Mackay, Qld, Australia, 4740

122000 OFFSET STANDARD DUTY